



Product Specification and Technical Data

PRODUCT: BG EPR™ Engine Performance Restoration™

PART NO.: 109

TEST DATA:	Test	ASTM Test Method	Typical Test Results
	API Gravity @ 15.6°C (60°F)	D 287	29.8
	Specific Gravity @ 15.6°C (60°F).	D 1298	0.8773
	Density,		
	U.S. lbs./gal. (kg/L) @ 15.6°C (60°F)	D 1250	7.314
	Flash Point, PMCC	D 93	43°C (110°F)
	Pour Point	D 97	-21°C (-5°F)
	Color	D 1500	L0.5
	Color	Visual.	Light Amber

PROBLEM: High operating temperatures, reduced engine cooling and prolonged drain intervals take their toll on today’s automotive engine oils. Continuous thermal and oxidative breakdown contributes to oil thickening, heat retention and deposit formation. These heavy deposits can impede normal piston ring function; thus reducing fuel economy, lowering power output, and increasing harmful exhaust emissions and oil consumption.

Gasoline Direct Injection engines are specifically prone to early deposit buildup on the piston surface, intake ports and valves. As early as 20,000 miles, deposits in GDI engines can cause dramatic efficiency losses and low-mileage misfire codes.

SOLUTION: BG EPR™ ENGINE PERFORMANCE RESTORATION™ softens and dissolves hard-to-remove deposits from piston rings in as little as 10 minutes! Properly sealed combustion chambers improve compression and reduce oil dilution through blow-by. BG EPR™ cleans micro passageways to maintain the critical hydraulic function of components such as valve train actuators and turbochargers. BG EPR™ restores fuel economy and power and is harmless to seals and other engine components. Excellent for maintenance of Gasoline Direct Injection engines.

- BENEFITS:**
- Removes carbon deposits
 - Restores compression
 - Lowers tailpipe emissions
 - Reduces oil consumption by restoring ring function
 - Improves overall power and engine efficiency
 - Harmless to oil pumps, seals and gaskets

USAGE: **For 4–6 quart (3.7–5.6 liter) capacity crankcase:** Add one 11 oz. (325 mL) can BG EPR™ to crankcase. Start engine, bring to full operating temperature and run engine for another 10 minutes at 1,200 RPM. Shut off engine, drain oil and remove old oil filter. Install new filter, replace drain plug, and fill with new oil. Do not use on badly sludged engines!

For 7-9 quart (6.6–8.5 liter) capacity crankcase: Add two 11 oz. (325 mL) cans BG EPR™ to crankcase. Start engine, bring to full operating temperature and run engine for another 20 minutes at 1,200 RPM. Shut off engine, drain oil and remove old oil filter. Install new filter, replace drain plug, and fill with new oil. Do not use on badly sludged engines!

For 10–16 quart (9.4–15.1 liter) capacity crankcase: Add one 32 oz. (946 mL) bottle BG EPR™ to crankcase. Start engine, bring to full operating temperature and run engine for a minimum of 45 minutes at 1,200 RPM. Shut off engine, drain oil and remove old oil filter. Install new filter, replace drain plug, and fill with new oil. Do not use on badly sludged engines!

BG Products, Inc., accepts no liability for excessive use or misuse of this product.