



Product Specification and Technical Data

PRODUCT: BG SAE 5W-30 Full Synthetic Engine Oil

PART NO.: 737

PERFORMANCE

CRITERIA: It meets or exceeds most European performance specifications including ACEA A5/B5-12 (2012), ACEA C3-12 (2012), ACEA C2-12 (2012), API SN, MB-Approval 229.51, MB-APPROVAL 229.52, Volkswagen VW50200 (2005), Volkswagen VW50500 (2005), Volkswagen VW50501 (2005), BMW Longlife-04, Porsche, PSA Peugeot Citroën B712290, GM Dexos 2.

TEST DATA:	Test	ASTM Test Method	Typical Test Results
	API Gravity @ 15.6°C (60°F)	D287	34.7
	Specific Gravity @ 15.6°C (60°F)	D1298	0.8513
	Density,		
	U.S. lbs./gal. @ 15.6°C (60°F)	D1250	7.097
	Viscosity, cSt @ 40°C (104°F)	D445	67.08
	Viscosity, cSt @ 100°C (212°F)	D445	11.59
	Viscosity Index	D2270	169
	Viscosity, cP @ 150°C (302°F)HT/HS	D4683	3.66
	Flash Point, C0C	D92	228°C (442°F)
	Viscosity, cP @ -30°C (-22°F)	D5293	5626
	Pour Point	D97	-34°C (-30°F)
	Noack Volatility, % Loss	D5800	8.7
	Color	D1500	3.0
	Color	Visual	Amber

DESCRIPTION: BG SAE 5W-30 Full Synthetic Engine Oil is an exclusive formulation that meets both stringent European specifications and API SN. It offers superior performance in gasoline and diesel passenger car engines. Its enhanced thermal and oxidative stability allow for extended drain intervals. BG SAE 5W-30 Full Synthetic Engine Oil flows immediately to lubricate vital engine components for easy cold weather starts and provides outstanding high temperature protection. Fulfills performance requirements for API service standard SN for gasoline engine oils.

USAGE: Use in accordance with manufacturer’s recommendations.

BG Products, Inc., accepts no liability for excessive use or misuse of this product.